

# AGRIMAX RT 657

<b>TIRE SIZE</b>	<b>320/65 R 18</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	125 A8/B



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94073252	<b>RC (IN)</b>	105.0
<b>SW (IN)</b>	12.2	<b>RIM REC</b>	W 10
<b>OD (IN)</b>	34.8	<b>RIM ALT</b>	W 9 ; W 11
<b>SLR (IN)</b>	15.7	<b>ECE</b>	E11-106R-008145

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	47
<b>30</b>	1200	1420	1640	1820	2040	2230	2660	2950	3320	3640
<b>25</b>	1200	1420	1640	1820	2040	2230	2660	2950	3320	3640
<b>20</b>	1290	1530	1760	1950	2190	2380	2850	3160	3560	3900
<b>5 LT</b>	1620	1910	2200	2450	2740	2990	3570	3960	4450	4880
<b>5 HT</b>	1290	1530	1760	1950	2190	2380	2850	3160	3560	3900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.