


AGRIMAX V- FLECTO

TIRE SIZE	VF 600/60 R 30
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR DE ALTA POTENCIA / TRACTOR
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	158 D



DIMENSIONES US STANDARD

CÓDIGO USA	94053360	RC (IN)	173.4
SW (IN)	23.4	RIM REC	DW 20 B
OD (IN)	58.5	RIM ALT	DW 18 L; DW 21 B
SLR (IN)	25.6	ECE	E11-106R-002979

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
45	4670	5460	6220	6990	7750	8520
FROM 40 TO 25	5150	6000	6830	7680	8520	9370
20	5250	6110	6970	7830	8690	9560
12	5350	6230	7100	7980	8850	9740
5	5650	6590	7520	8440	9370	10310
*UPTO 5 CYC WITH FRONT LOADER	7210	8390	9570	10750	11930	13120
5 HT	5250	6110	6970	7830	8690	9560

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.