

## STAR TRAC

|                  |                                         |
|------------------|-----------------------------------------|
| <b>TIRE SIZE</b> | <b>VA 500/95 D 32</b>                   |
| <b>UM</b>        | IS STANDARD                             |
| <b>MACHINERY</b> | COSECHADORA DE ALGODÓN /<br>COSECHADORA |
| <b>VERSIÓN</b>   | STANDARD                                |
| <b>TIRE TYPE</b> | TL                                      |
| <b>LI/SS</b>     | 179 A8 ; 186 A5                         |



### DIMENSIONES IS STANDARD

|                 |      |                |          |
|-----------------|------|----------------|----------|
| <b>SW (MM)</b>  | 500  | <b>RIM REC</b> | 13.00 VA |
| <b>OD (MM)</b>  | 1836 |                |          |
| <b>SLR (MM)</b> | 809  |                |          |
| <b>RC (MM)</b>  | 5324 |                |          |

### LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>4.20</b> |
| 40                | 7750        |
| 25                | 9500        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.