

# AS 504

<b>TIRE SIZE</b>	7.00 - 12
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	LEVANTADOR TELESCÓPICO / REBOQUE PARA OS CAMPOS / IMPLEMENTOS AGRÍCOLAS / LEVANTADOR TELESCÓPICO
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TT
<b>LI/SS DRIVE WHEEL</b>	75 A8
<b>LI/SS FREE ROLLING</b>	88 A8



## DIMENSÕES IS STANDARD

<b>SW (MM)</b>	187	<b>RIM REC</b>	4.5
<b>OD (MM)</b>	683	<b>ECE</b>	E4-106R-002207
<b>SLR (MM)</b>	311	<b>PR</b>	4
<b>RC (MM)</b>	2049		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.70
10 FR	785
25 FR	665
30 FR	625
40 FR	560
10 DW	540
25 DW	460
30 DW	430
40 DW	385

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.