DATA SHEET

PRINTED ON
23-04-2026

AT 171

	35X10 - 18
UM	US STANDARD
CONSTRUCTION	BIAS
MACHINERY	ATV / ÇAMUR BATAKLIK TRAKTÖRÜ / TRAKTÖR
VERSION	STANDARD
TIRE TYPE	TL
	90 A8 ; 66 F

UNDEFINED US STANDARD

USA CODE	94055166	**RC (IN)**	104.2
SW (IN)	9.5	**RIM REC**	W 8
OD (IN)	35.4	**PR**	8
SLR (IN)	16.4	**TRA CODE**	R1W+

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	20	15
25 MUD BOGGING	1325	-
50 MUD BOGGING	665	-
25 CASUAL TRANSPORT	-	1080
50 CASUL TRANSPORT	-	540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..