

AGRIMAX FORCE

TIRE SIZE	IF 900/60 R 38 CFO
UM	US STANDARD
MACHINERY	COSECHADORA / TRACTOR DE ALTA POTENCIA / TRACTOR
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	184 D

DIMENSIONES US STANDARD

CÓDIGO USA	94038749	RC (IN)	240.4
SW (IN)	36.1	RIM REC	DW 30 A ; DW 30 B
OD (IN)	80.5	RIM ALT	TW 31 B
SLR (IN)	35.6	ECE	E11-106R-006493

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	8300	9570	11010	12270	13710	14980	16790	18050
FROM 40 TO 25	9130	10520	12100	13490	15080	16470	18450	19800
20	9490	10930	12580	14020	15670	17120	19180	20630
12	9850	11350	13060	14560	16280	17780	19920	21430
5	11580	13350	15370	17130	19150	20910	23420	25200
UPTO 20 CYC	11860	13670	15730	17540	19600	21410	23980	25790
UPTO 10 CYC	14140	16290	18750	20910	23370	25520	28590	30750
UPTO 5 CYC	15510	17870	20570	22930	25630	27990	31360	33730
5 HT	9490	10930	12580	14020	15670	17120	19180	20630

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

