

# FLOTATION 648

<b>TIRE SIZE</b>	500/50 - 17
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	BIAS
<b>MACHINERY</b>	PRESSA PER BALLE DI FIENO / MIETITREBBIA / SPARGITORE / MIETITREBBIA / ATTREZZI AGRICOLI
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	128 A8/124 B
<b>LI/SS FREE ROLLING</b>	140 A8/136 B



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94039814	<b>RC (IN)</b>	108.3
<b>SW (IN)</b>	20.1	<b>RIM REC</b>	16.00
<b>OD (IN)</b>	37.2	<b>ECE</b>	E4-106R-002713
<b>SLR (IN)</b>	16.4	<b>PR</b>	10

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	22	25	29
5 FR	6530	7020	7720
10 FR	5870	6320	6940
20 FR	5220	5620	6170
25 FR	4660	5020	5510
30 FR	4200	4520	4940
5 DW	4700	5050	5560
10 DW	4220	4540	5000
20 DW	3750	4030	4440
25 DW	3350	3600	3970
30 DW	3020	3240	3530

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.