


FLOTATION 648

TIRE SIZE	385/65 - 22.5
UM	IS STANDARD
CONSTRUCTION	 BIAS
MACHINERY	EMPACADORA DE HENO / COSECHADORA / ESPARCIDOR / COSECHADORA / MAQUINARIA AGRÍCOLA
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	148 A8/144 B
LI/SS FREE ROLLING	160 A8/ 156 B



DIMENSIONES IS STANDARD

SW (MM)	400	RIM REC	AG 11.75
OD (MM)	1070	ECE	E4-106R-002263
SLR (MM)	475	PR	18
RC (MM)	3233		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.80	4.00	4.30
10 FR	5860	6040	6300
20 FR	5275	5435	5670
30 FR	4685	4835	5040
40 FR	4185	4315	4500
50 FR	3765	3885	4000
10 DW	4100	4230	4410
20 DW	3690	3805	3970
30 DW	3280	3380	3530
40 DW	2930	3020	3150
50 DW	2635	2720	2800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.