


AGRIMAX V- FLECTO



| | |
|---------------------|--|
| TIRE SIZE | VF 710/75 R 42 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTEUR DE FORTE PUISSANCE / TRACTEUR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 184 D |

DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|------------------|
| CODE USA | 94075447 | RC (IN) | 252.4 |
| SW (IN) | 28.7 | RIM REC | DW 24 B |
| OD (IN) | 84.6 | RIM ALT | DW 23 B; DW 25 B |
| SLR (IN) | 36.9 | ECE | E11-106R-009074 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 |
|--------------------------------------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 9030 | 10470 | 11920 | 13540 | 14980 | 16420 | 18050 |
| FROM 40 TO 25 | 9920 | 11510 | 13090 | 14880 | 16470 | 18050 | 19840 |
| 20 | 10120 | 11730 | 13350 | 15180 | 16790 | 18410 | 20240 |
| 12 | 10320 | 11960 | 13610 | 15480 | 17120 | 18770 | 20630 |
| 5 | 10910 | 12650 | 14400 | 16370 | 18110 | 19850 | 21820 |
| *UPTO 5 CYC WITH FRONT LOADER | 13890 | 16100 | 18330 | 20830 | 23050 | 25270 | 27780 |
| 5 HT | 10120 | 11730 | 13350 | 15180 | 16790 | 18410 | 20240 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.