

# RIB 774 (A)

|                           |   |
|---------------------------|---|
| <b>TIRE SIZE</b>          | 200/60 - 14.5   |
| <b>UM</b>                 | US STANDARD   |
| <b>CONSTRUCTION</b>       | ⊠ BIAS  |
| <b>MACHINERY</b>          | ПРЕСС-ПОДБОРЩИК / КОМБАЙН<br>/ ПРИЦЕП / КОМБАЙН /<br>СЕЛЬСКОХОЗЯЙСТВЕННОЕ<br>ОБОРУДОВАНИЕ |
| <b>VERSION</b>            | HD  |
| <b>TIRE TYPE</b>          | TT  |
| <b>LI/SS FREE ROLLING</b> | 106 A8  |



## РАЗМЕРЫ US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94053216 | <b>RC (IN)</b> | 74.3            |
| <b>SW (IN)</b>  | 8.3      | <b>RIM REC</b> | AG 6.75         |
| <b>OD (IN)</b>  | 24.0     | <b>ECE</b>     | E11-106R-005259 |
| <b>SLR (IN)</b> | 11.3     | <b>PR</b>      | 10              |

## LOAD CAPACITY (LBS/TIRE)

| <b>MPH / PSI</b> | <b>73</b> |
|------------------|-----------|
| 5 FR             | 2930      |
| 15 FR            | 2490      |
| 20 FR            | 2350      |
| 25 FR            | 2090      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.