

RIDEMAX FL 693 M

710/35 R 22.5

UM US STANDARD

CONSTRUCTION  RADIAL

MACHINERY TANKER / RÖMORK / UYGULAMALI
MAKINE

VERSION STANDARD

TIRE TYPE TL

157 D ; 154 E



UNDEFINED US STANDARD

USA CODE	94056132	RC (IN)	128.1
SW (IN)	28.0	RIM REC	AG 24.00
OD (IN)	42.1	ECE	E11-106R-004758
SLR (IN)	19.0		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	15	17	23	29	35	41	46	52	58
45	3020	3390	4220	4790	5540	6280	6870	7530	8270
40	3330	3740	4640	5280	6100	6910	7550	8280	9090
30	4020	4520	5620	6390	7390	8380	9150	10030	11010
25	4520	5080	6320	7180	8290	9400	10270	11260	12370
20	5020	5630	7010	7970	9200	10440	11410	12500	13730
15	5250	5900	7340	8340	9630	10930	11940	13080	14370
5	5990	6710	8360	9500	10970	12440	13590	14900	16370

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.