

# AS 504

<b>TIRE SIZE</b>	<b>11.5/80 - 15.3</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	BIAS
<b>MACHINERY</b>	TELESKOPLADER / FELD-ANHÄNGER / LANDWIRTSCHAFTLICHE GERÄTE / TELESKOPLADER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	119 A8
<b>LI/SS FREE ROLLING</b>	131 A8



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94018703	<b>RC (IN)</b>	100.0
<b>SW (IN)</b>	11.4	<b>RIM REC</b>	9.00
<b>OD (IN)</b>	34.1	<b>PR</b>	10
<b>SLR (IN)</b>	15.0		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	49
5 FR	6020
15 FR	5110
20 FR	4820
25 FR	4300
5 DW	4200
15 DW	3570
20 DW	3360
25 DW	3000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.