

AGRIMAX RT 765

480/70 R 34**UM** US STANDARD**CONSTRUCTION**  RADIAL**MACHINERY** İLAÇLAMA / TRAKTÖR / ÜZÜM HASAT
MAKINESİ / BIÇERDÖVER /
UYGULAMALI MAKİNE**VERSION** SPECIAL**TIRE TYPE** TL

149 D



UNDEFINED US STANDARD

USA CODE	94062300	RC (IN)	187.9
SW (IN)	18.9	RIM REC	W 15 L
OD (IN)	62.2	RIM ALT	W 14 L; W 16 L
SLR (IN)	28.0	ECE	E11-106R-005524

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
40	3370	3870	4440	5020	5590	6160	6730	7160
30	3550	4070	4670	5280	5870	6480	7090	7530
25	3690	4240	4870	5500	6130	6760	7390	7850
20	3880	4450	5110	5780	6440	7100	7760	8240
5 LT	4520	5190	5960	6720	7500	8270	9030	9600
5 HT	3880	4450	5110	5780	6440	7100	7760	8240

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.