

# XL GRIP (BHL)

|                     |                           |
|---------------------|---------------------------|
| <b>TIRE SIZE</b>    | <b>16.9 - 28</b>          |
| <b>UM</b>           | US STANDARD               |
| <b>CONSTRUCTION</b> | ⊠ BIAS                    |
| <b>MACHINERY</b>    | CARGADORA RETROEXCAVADORA |
| <b>VERSIÓN</b>      | INDUSTRIAL                |
| <b>TIRE TYPE</b>    | TT                        |
| <b>LI/SS</b>        | 152 A8                    |



## DIMENSIONES US STANDARD

|                   |          |                |        |
|-------------------|----------|----------------|--------|
| <b>CÓDIGO USA</b> | 94043873 | <b>RIM REC</b> | DW 15L |
| <b>OD (IN)</b>    | 55.1     | <b>RIM ALT</b> | DW 14L |
| <b>SLR (IN)</b>   | 25.2     | <b>PR</b>      | 12     |
| <b>RC (IN)</b>    | 164.4    |                |        |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>38</b> |
| 25               | 7830      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.