

# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>340/85 R 36</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	132 A8/B



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94033089	<b>RC (IN)</b>	177.4
<b>SW (IN)</b>	13.9	<b>RIM REC</b>	W 12
<b>OD (IN)</b>	58.7	<b>RIM ALT</b>	W 11
<b>SLR (IN)</b>	27.1	<b>ECE</b>	E4-106R-000763

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
<b>30</b>	2420	2820	3220	3620	4010	4410
<b>25</b>	2420	2820	3220	3620	4010	4410
<b>20</b>	2600	3020	3450	3870	4300	4720
<b>5 LT</b>	3250	3790	4320	4850	5380	5910
<b>5 HT</b>	2600	3020	3450	3870	4300	4720

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.