

# AGRIMAX RT 855

|                  |                                                                       |
|------------------|-----------------------------------------------------------------------|
| <b>TIRE SIZE</b> | <b>250/85 R 28</b>                                                    |
| <b>UM</b>        | US STANDARD                                                           |
| <b>MACHINERY</b> | SPRAYER / VINEYARD HARVESTER /<br>TRACTOR / HARVESTER /<br>IMPLEMENTS |
| <b>VERSION</b>   | SPECIAL                                                               |
| <b>TL/TT</b>     | TL                                                                    |
| <b>LI/SS</b>     | 112 A8/B                                                              |



## DIMENSIONS US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94047666 | <b>RC (IN)</b> | 134.7          |
| <b>SW (IN)</b>  | 9.9      | <b>RIM REC</b> | W 8            |
| <b>OD (IN)</b>  | 44.8     | <b>RIM ALT</b> | W 7 ; W 9      |
| <b>SLR (IN)</b> | 20.4     | <b>ECE</b>     | E4-106R-000646 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI   | 9    | 12   | 15   | 17   | 20   | 23   |
|-------------|------|------|------|------|------|------|
| <b>30</b>   | 1370 | 1590 | 1810 | 2030 | 2250 | 2470 |
| <b>25</b>   | 1370 | 1590 | 1810 | 2030 | 2250 | 2470 |
| <b>20</b>   | 1450 | 1700 | 1940 | 2170 | 2410 | 2650 |
| <b>5 LT</b> | 1830 | 2130 | 2420 | 2720 | 3020 | 3320 |
| <b>5 HT</b> | 1450 | 1700 | 1940 | 2170 | 2410 | 2650 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.