


# AGRIMAX RT 945

<b>TYRE SIZE</b>	<b>380/90 R 46</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SPRAYER / TRACTOR / IMPLEMENTS
<b>VERSION</b>	SPECIAL
<b>TL/TT</b>	TL
<b>LI/SS</b>	159 A8/B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94033171	<b>RC (IN)</b>	224.4
<b>SW (IN)</b>	15.0	<b>RIM REC</b>	W 12
<b>OD (IN)</b>	72.9	<b>RIM ALT</b>	W 11 ; W 13
<b>SLR (IN)</b>	33.8	<b>ECE</b>	E4-106R-001409

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	12	17	23	29	35	41	46	52	58	64
30	3940	5050	6150	6760	7260	7950	8540	8970	9640	-
25	3940	5050	6150	6760	7260	7950	8540	8970	9640	-
20	4210	5400	6590	7230	7780	8510	9150	9610	10330	-
5	4620	6030	7310	8720	10010	10390	11540	12820	13320	14470

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.