

## AGRIMAX RT 855

|                  |                                                                       |
|------------------|-----------------------------------------------------------------------|
| <b>TIRE SIZE</b> | <b>520/85 R 42</b>                                                    |
| <b>UM</b>        | IS STANDARD                                                           |
| <b>MACHINERY</b> | SPRAYER / VINEYARD HARVESTER /<br>TRACTOR / HARVESTER /<br>IMPLEMENTS |
| <b>VERSION</b>   | STANDARD                                                              |
| <b>TL/TT</b>     | TL                                                                    |
| <b>LI/SS</b>     | 167 A8/B                                                              |



### DIMENSIONS IS STANDARD

|                 |      |                |                                    |
|-----------------|------|----------------|------------------------------------|
| <b>SW (MM)</b>  | 540  | <b>RIM REC</b> | DW 16 L ; W 16 A ; DD 16           |
| <b>OD (MM)</b>  | 1951 | <b>RIM ALT</b> | DW 18 A ; DD 18 ; W 18 A ; DD 18 L |
| <b>SLR (MM)</b> | 895  | <b>ECE</b>     | E4-106R-001491                     |
| <b>RC (MM)</b>  | 5919 | <b>SRI</b>     | 925                                |

### LOAD CAPACITY (KG/TIRE)

| KM/H / BAR   | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.4  | 2.8  | 3.2  |
|--------------|------|------|------|------|------|------|------|------|------|
| <b>50</b>    | 2270 | 2640 | 3015 | 3385 | 3755 | 4125 | 4635 | 5070 | 5450 |
| <b>40</b>    | 2270 | 2640 | 3015 | 3385 | 3755 | 4125 | 4635 | 5070 | 5450 |
| <b>30</b>    | 2430 | 2830 | 3225 | 3625 | 4020 | 4415 | 4960 | 5425 | 5830 |
| <b>10 LT</b> | 3045 | 3540 | 4040 | 4535 | 5035 | 5530 | 6210 | 6795 | 7305 |
| <b>10 HT</b> | 2430 | 2830 | 3225 | 3625 | 4020 | 4415 | 4960 | 5425 | 5830 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.