


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>520/85 R 46</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZATOR / MAȘINĂ DE RECOLTAT PODGORII / TRACTOR / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	158 A8/B



## DIMENSIUNI IS STANDARD

<b>SW (MM)</b>	516	<b>RIM REC</b>	DW 16 L; W 16 A; W 16 L; DD 16
<b>OD (MM)</b>	2052	<b>RIM ALT</b>	DW 18 L; W 18 L; W 18 A
<b>SLR (MM)</b>	930	<b>ECE</b>	E4-106R-001415
<b>RC (MM)</b>	6157	<b>SRI</b>	975

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
50	2340	2720	3105	3485	3870	4250
40	2340	2720	3105	3485	3870	4250
30	2505	2915	3325	3735	4145	4550
10 LT	3135	3645	4160	4670	5185	5695
10 HT	2505	2915	3325	3735	4145	4550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.