


# AGRIMAX SPARGO

<b>TIRE SIZE</b>	<b>VF 380/90 R 46 CFO</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRATTORE
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	173 D



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94519231	<b>RC (IN)</b>	220.9
<b>SW (IN)</b>	15.4	<b>RIM REC</b>	DW 13 A
<b>OD (IN)</b>	72.9	<b>RIM ALT</b>	W 13 A ; DW 12
<b>SLR (IN)</b>	33.3	<b>ECE</b>	E4-106R-000796

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	14	12	20	23	26	29	32	35	38	41	44	47	49	52	55	58	61	64
45	5620	6270	7050	7700	8100	8480	8750	9010	9460	9930	10310	10710	11030	11360	11680	12010	12530	13040
<b>FROM 40 TO 25</b>	6170	6880	7740	8460	8890	9320	9610	9890	10400	10900	11330	11750	12120	12470	12840	13190	13760	14330
20	6300	7030	7910	8640	9080	9510	9800	10090	10610	11120	11560	12000	12360	12720	13090	13450	14040	14620
12	6420	7160	8060	8800	9250	9690	9990	10290	10820	11340	11790	12230	12600	12980	13350	13720	14310	14910
5*	6780	7580	8530	9310	9780	10260	10580	10880	11440	11990	12460	12930	13330	13730	14110	14510	15140	15770
<b>UPTO 10 CYC.</b>	8610	9620	10820	11810	12420	13010	13420	13820	14510	15220	15810	16420	16910	17420	17920	18410	19220	20010
<b>UPTO 20 CYC.</b>	7210	8050	9050	9890	10400	10900	11240	11570	12150	12750	13240	13750	14170	14590	15010	15430	16100	16760

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.