


# AGRIMAX SPARGO

**VF 380/105 R 54**

<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRAKTÖR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	180 D



## UNDEFINED IS STANDARD

<b>SW (MM)</b>	400	<b>RIM REC</b>	W 13 A
<b>OD (MM)</b>	2140	<b>RIM ALT</b>	W 12; DW 12; DW 13; DW 13 L
<b>SLR (MM)</b>	984	<b>ECE</b>	E11-106R-0010148
<b>RC (MM)</b>	6503	<b>SRI</b>	1025

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.4	1.6	1.8	2	2.2	2.4	2.6	2.8	3	3.2	3.4	3.6	3.8	4	4.2	4.4
<b>70</b>	3495	3930	4295	4515	4730	4875	5020	5275	5530	5750	5970	6330	6405	6550	6695	6985	7275
<b>FROM 65 TO 40</b>	3840	4320	4720	4960	5200	5360	5520	5800	6080	6320	6560	6960	7040	7200	7360	7680	8000
<b>30</b>	3920	4410	4815	5060	5305	5470	5635	5920	6205	6450	6695	7100	7185	7345	7510	7835	8160
<b>20</b>	3995	4495	4910	5160	5410	5575	5745	6035	6325	6575	6825	7240	7325	7490	7655	7990	8320
<b>10</b>	4225	4755	5195	5460	5720	5900	6075	6380	6690	6955	7220	7660	7745	7920	8100	8450	8800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.