

AS 504

TIRE SIZE	12.5/80 - 18
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	129 A8
LI/SS FREE ROLLING	142 A8



РАЗМЕРЫ US STANDARD

USA CODE	94018789	RC (IN)	113.9
SW (IN)	12.1	RIM REC	W 9
OD (IN)	38.9	RIM ALT	9; 11
SLR (IN)	17.2	ECE	E4-106R-001904

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	54
5 FR	8180
15 FR	6960
20 FR	6550
25 FR	5840
5 DW	5710
15 DW	4850
20 DW	4560
25 DW	4080

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.