


# EARTHMAX SR 30

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 29.5 R 25  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | ARTICULATED DUMP TRUCK / DOZER /<br>LOADER   |
| <b>VERSION</b>      | CUT RESISTANT COMPOUND   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 200 B  |



## DIMENSIONS US STANDARD

|                 |          |                    |           |
|-----------------|----------|--------------------|-----------|
| <b>USA CODE</b> | 94054473 | <b>RIM REC</b>     | 25.00/3.5 |
| <b>OD (IN)</b>  | 73.3     | <b>TRA CODE</b>    | E3        |
| <b>SLR (IN)</b> | 32.2     | <b>STAR RATING</b> | ★★        |
| <b>RC (IN)</b>  | 218.7    |                    |           |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 58    | 62    | 65    | 69    | 73    | 76    |
|-----------|-------|-------|-------|-------|-------|-------|
| 30        | 25400 | 26000 | 27600 | 28300 | 30000 | 30900 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.