


# AGRIMAX FORCE



<b>TYRE SIZE</b>	<b>IF 480/95 R 50</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HIGH-POWER TRACTOR / TRACTOR
<b>VERSION</b>	STANDARD
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	170 D

## DIMENSIONS US STANDARD

<b>USA CODE</b>	94058006	<b>RC (IN)</b>	258.8
<b>SW (IN)</b>	18.9	<b>RIM REC</b>	DW 16 B
<b>OD (IN)</b>	85.4	<b>ECE</b>	E11-106R-004898
<b>SLR (IN)</b>	39.4	<b>TRA CODE</b>	R1W

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	5650	6490	7460	8420	9380	10350	11310	12040
<b>FROM 40 TO 25</b>	6220	7140	8200	9260	10320	11380	12430	13200
20	6460	7420	8520	9620	10720	11830	12930	13760
12	6710	7700	8850	10000	11130	12280	13430	14290
5	7890	9060	10410	11750	13090	14440	15780	16800
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	8700	10000	11470	12960	14440	15920	17400	18520
5HT	6460	7420	8520	9620	10720	11830	12930	13760

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.