



IS standard



GROWING TOGETHER

RT 857



PRODUCT DATA SHEET



Radial

R-1

A8/B

145

Technologies



Strong Casing



Special Compound

Performance



Cut and Chip Resistance



Durability



Traction



High Load Capacity



RT 857

🇬🇧 RT 857 is a tire designed for soil tillage applications. Its strong casing offers excellent durability and traction. The stubble-resistant tread compound features high cut-and-chip resistance.

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 24"	320/85 R 24 (12.4 R 24)	122 A8/B	W 11	W 10 ; W 9	329	1154	528	3449	550	STD
	380/85 R 24 (14.9 R 24)	131 A8/B	W 12	W 13 ; W 11	380	1256	566	3783	600	STD
Ø 26"	420/85 R 26 (16.9 R 26)	138 A8/B	DW 15 L	W 14 L ; W 15 L ; W 16 L ; DW 16 L	450	1374	616	4115	650	STD
	460/85 R 26 (18.4 R 26)	143 A8/B	DW 15 L	W 15 L ; W 16 L ; DW 16 L	465	1442	642	4297	675	STD
Ø 28"	320/85 R 28 (12.4 R 28)	124 A8/B	W 11	W 9 ; W 10	329	1255	577	3779	600	STD
	340/85 R 28 (13.6 R 28)	127 A8/B	W 12	W 11	353	1289	599	3908	625	STD
	380/85 R 28 (14.9 R 28)	133 A8/B	W 12	W 11 ; W 13	390	1357	617	4127	650	STD
	420/85 R 28 (16.9 R 28)	139 A8/B	W 15 L	W 14 L ; W 13	450	1425	640	4276	675	STD
Ø 30"	420/85 R 30 (16.9 R 30)	140 A8/B	W 15 L	W 14 L ; W 13	450	1476	656	4398	700	STD
	460/85 R 30 (18.4 R 30)	145 A8/B	W 16 L	W 15 L ; W 14 L	475	1544	697	4648	725	STD

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index