

FLOTATION 648

| | |
|---------------------------|---|
| TIRE SIZE | 400/60 - 22.5 |
| UM | US STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | PRESSE À PAILLE / MOISSONNEUSE / ÉPANDEUR / MOISSONNEUSE / OUTILLAGE AGRICOLE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 155 A8/151 B |
| LI/SS FREE ROLLING | 167 A8/163 B |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| CODE USA | 94048618 | RC (IN) | 127.3 |
| SW (IN) | 15.7 | RIM REC | AG 11.75 |
| OD (IN) | 42.1 | ECE | E11-106R-004389 |
| SLR (IN) | 18.7 | PR | 22 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 77 | 81 | 86 |
|--------------|-------|-------|-------|
| 5 FR | 15810 | 16310 | 16820 |
| 10 FR | 14220 | 14680 | 15130 |
| 20 FR | 12640 | 13050 | 13460 |
| 25 FR | 11290 | 11650 | 12010 |
| 30 FR | 10160 | 10480 | 10750 |
| 5 DW | 11230 | 11610 | 11960 |
| 10 DW | 10110 | 10450 | 10770 |
| 20 DW | 8980 | 9280 | 9570 |
| 25 DW | 8020 | 8290 | 8540 |
| 30 DW | 7220 | 7460 | 7610 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.