

AGRIMAX SIRIO

TYRE SIZE	710/70 R 38
UM	IS STANDARD
MACHINERY	HIGH-POWER TRACTOR / TRACTOR
VERSION	HIGH SPEED
TL/TT	TL
LI/SS	171 D ; 168 E



DIMENSIONS IS STANDARD

SW (MM)	716	ECE	E4-106R-000818
OD (MM)	1959	SRI	925
SLR (MM)	887	TRA CODE	R1W
RC (MM)	5840	TREAD DEPTH (MM)	61,5
RIM REC	DW 23 B	TKPH (TK/H)	0
RIM ALT	DW 25 B		

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	2635	3025	3475	3920	4370	4820	5210	5600
65	2895	3325	3815	4305	4800	5290	5720	6150
50	3040	3490	4010	4525	5040	5560	6010	6460
40	3170	3640	4180	4715	5255	5795	6265	6735
25	3430	3940	4520	5105	5690	6270	6780	7290
10	4340	4985	5720	6460	7200	7935	8580	9225

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.