

# FLOTATION RIB 774



<b>TIRE SIZE</b>	<b>600/55 - 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	MOISSONNEUSE / REMORQUE / MOISSONNEUSE / OUTILLAGE AGRICOLE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	169 A8/166 B

## DIMENSIONS US STANDARD

<b>CODE USA</b>	94006632	<b>RC (IN)</b>	146.3
<b>SW (IN)</b>	23.6	<b>RIM REC</b>	AG 20.00
<b>OD (IN)</b>	48.4	<b>ECE</b>	E11-106R-005944
<b>SLR (IN)</b>	21.3	<b>PR</b>	16

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	32	35	38
<b>5 FR</b>	16240	17080	17900
<b>10 FR</b>	14620	15380	16110
<b>20 FR</b>	12980	13670	14320
<b>25 FR</b>	11600	12200	12790
<b>30 FR</b>	10440	10980	11680

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.