


EARTHMAX SR 41

| | |
|---------------------|--|
| TIRE SIZE | 29.5 R 25 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | CAMION À BENNE BASCULANTE / BULLDOZER / CHARGEUR / CHARGEUR |
| VERSION | CUT RESISTANT COMPOUND |
| TIRE TYPE | TL |
| LI/SS | 200 B ; 208 A2 |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|-----------|--------------------|-------|
| OD (MM) | 1862 | TRA CODE | E4/L4 |
| SLR (MM) | 830 | STAR RATING | ★★★ |
| RC (MM) | 5510 | | |
| RIM REC | 25.00/3.5 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 4.00 | 4.25 | 4.50 | 4.75 | 5.00 | 5.25 |
|------------|-------|-------|-------|-------|-------|-------|
| 50 | 11500 | 11800 | 12500 | 12850 | 13600 | 14000 |
| 10 | 15500 | 16000 | 17000 | 17500 | 18000 | -- |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.