


AGRIMAXFACTOR

| | |
|---------------------|--|
| TIRE SIZE | 480/70 R 34 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 155 D ; 158 A8 |



ABMESSUNGEN IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 479 | RIM REC | W 15 L |
| OD (MM) | 1580 | RIM ALT | W 14 L ; W 16 L |
| SLR (MM) | 729 | ECE | E11-106R-007643 |
| RC (MM) | 4761 | SRI | 750 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 |
|------------|------|------|------|------|------|------|------|------|------|------|
| 65 | 1515 | 1785 | 2055 | 2290 | 2560 | 2790 | 3065 | 3295 | 3605 | 3875 |
| 50 | 1590 | 1875 | 2160 | 2405 | 2690 | 2935 | 3220 | 3460 | 3790 | 4070 |
| 40 | 1660 | 1955 | 2250 | 2505 | 2805 | 3060 | 3355 | 3610 | 3950 | 4245 |
| 30 | 1740 | 2055 | 2365 | 2635 | 2945 | 3215 | 3525 | 3795 | 4150 | 4460 |
| 10 LT | 2030 | 2390 | 2755 | 3070 | 3430 | 3745 | 4105 | 4420 | 4835 | 5195 |
| 10 HT | 1740 | 2055 | 2365 | 2635 | 2945 | 3215 | 3525 | 3795 | 4150 | 4460 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.