


FLOTATION 648

| | |
|---------------------------|--|
| TIRE SIZE | 400/60 - 22.5 |
| UM | IS STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | EMPACADORA DE HENO / COSECHADORA / ESPARCIDOR / COSECHADORA / MAQUINARIA AGRÍCOLA |
| VERSIÓN | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 144 A8/140 B |
| LI/SS FREE ROLLING | 156 A8/152 B |



DIMENSIONES IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 400 | RIM REC | AG 11.75 |
| OD (MM) | 1070 | ECE | E4-106R-002336 |
| SLR (MM) | 475 | PR | 16 |
| RC (MM) | 3233 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.50 | 2.50 | 3.50 |
|------------|------|------|------|
| 10 FR | 3410 | 4600 | 5600 |
| 20 FR | 3070 | 4140 | 5040 |
| 30 FR | 2725 | 3680 | 4480 |
| 40 FR | 2435 | 3285 | 4000 |
| 50 FR | 2190 | 2955 | 3550 |
| 10 DW | 2385 | 3220 | 3920 |
| 20 DW | 2150 | 2900 | 3530 |
| 30 DW | 1910 | 2575 | 3135 |
| 40 DW | 1705 | 2300 | 2800 |
| 50 DW | 1535 | 2070 | 2500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.