


AGRIMAX TERIS

| | |
|--------------|--|
| TIRE SIZE | IF 580/80 R 34 CFO |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | CEIFEIRA / COLHEDORA DE ALGODÃO |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 177 D |



DIMENSÕES US STANDARD

| | | | |
|------------|----------|---------|------------------|
| CÓDIGO USA | 94044641 | RC (IN) | 213.5 |
| SW (IN) | 23.1 | RIM REC | DW 20 B; DW 20 A |
| OD (IN) | 70.6 | RIM ALT | DW 21 A; DW 21 B |
| SLR (IN) | 31.9 | ECE | E4-106R-001833 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 | 41 | 46 | 52 |
|---------------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 5430 | 6310 | 7190 | 8220 | 9090 | 9970 | 10990 | 11580 | 12760 | 14650 | 20040 |
| FROM 40 TO 25 | 5970 | 6930 | 7900 | 9020 | 9990 | 10950 | 12070 | 12720 | 14010 | 16100 | 22030 |
| 20 | 6210 | 7210 | 8220 | 9390 | 10390 | 11390 | 12570 | 13240 | 14580 | 16750 | 22910 |
| 12 | 6440 | 7490 | 8530 | 9750 | 10790 | 11830 | 13040 | 13740 | 15130 | 17390 | 23790 |
| 5 | 7580 | 8800 | 10020 | 11460 | 12690 | 13920 | 15350 | 16160 | 17800 | 20450 | 27980 |
| UPTO 20 CYC* | 7750 | 9010 | 10270 | 11720 | 12980 | 14240 | 15700 | 16540 | 18210 | 20930 | 28620 |
| UPTO 10 CYC* | 9240 | 10740 | 12230 | 13980 | 15480 | 16970 | 18720 | 19710 | 21710 | 24950 | 34130 |
| 5 HT | 6210 | 7210 | 8220 | 9390 | 10390 | 11390 | 12570 | 13240 | 14580 | 16750 | 22910 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.