

AGRIMAX RT 765

| | |
|---------------------|--|
| TIRE SIZE | 620/70 R 46 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ОПРЫСКИВАТЕЛЬ / ТРАКТОР-ТЯГАЧ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ |
| VERSION | SPECIAL |
| TIRE TYPE | TL |
| LI/SS | 162 D |



РАЗМЕРЫ IS STANDARD

| | | | |
|-----------------|------|-----------------|-----------------|
| SW (MM) | 625 | RIM REC | DW 20 B |
| OD (MM) | 2036 | ECE | E11-106R-005999 |
| SLR (MM) | 924 | SRI | 975 |
| RC (MM) | 6106 | TRA CODE | R1W |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|------------|------|------|------|------|------|------|
| 65 | 2615 | 3040 | 3470 | 3895 | 4325 | 4750 |
| 50 | 2745 | 3195 | 3645 | 4095 | 4545 | 4990 |
| 40 | 2865 | 3335 | 3800 | 4270 | 4740 | 5205 |
| 30 | 3010 | 3500 | 3990 | 4485 | 4975 | 5465 |
| 10 LT | 3505 | 4075 | 4650 | 5220 | 5795 | 6365 |
| 10 HT | 3010 | 3500 | 3990 | 4485 | 4975 | 5465 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.