

# AGRIMAX RT 955

<b>TIRE SIZE</b>	<b>300/95 R 52</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZADOR AGRÍCOLA / VINDIMADORA / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	151 A8/B



## DIMENSÕES IS STANDARD

<b>SW (MM)</b>	295	<b>RIM REC</b>	W 9
<b>OD (MM)</b>	1891	<b>RIM ALT</b>	W 10; W 11; DW 10; DW 11
<b>SLR (MM)</b>	889	<b>ECE</b>	E4-106R-001484
<b>RC (MM)</b>	5774	<b>SRI</b>	900

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	1350	1760	2140	2350	2485	2730	2970	3210	3450	-
40	1350	1760	2140	2350	2485	2730	2970	3210	3450	-
30	1445	1885	2295	2515	2665	2920	3180	3440	3695	-
10	1605	2020	2485	2950	3420	3520	3935	4350	4765	5175

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.