

# AW 705

|                           |  |
|---------------------------|--|
| <b>TIRE SIZE</b>          | <b>400/55 - 22.5</b>   |
| <b>UM</b>                 | IS STANDARD  |
| <b>CONSTRUCTION</b>       | ⊠ BIAS   |
| <b>MACHINERY</b>          | PRESSA PER BALLE DI FIENO /<br>ATTREZZI AGRICOLI / RIMORCHIO /<br>MIETITREBBIA / ATTREZZI AGRICOLI |
| <b>VERSIONE</b>           | STUBBLE RESISTANT  |
| <b>TIRE TYPE</b>          | TL   |
| <b>LI/SS FREE ROLLING</b> | 156 A8   |



## DIMENSIONI IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 405  | <b>RIM REC</b> | AG 11.75        |
| <b>OD (MM)</b>  | 1016 | <b>RIM ALT</b> | 12.25; AG 13.00 |
| <b>SLR (MM)</b> | 443  | <b>PR</b>      | 20              |
| <b>RC (MM)</b>  | 3072 |                |                 |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>5.00</b> |
|-------------------|-------------|
| 10 FR             | 5600        |
| 25 FR             | 4760        |
| 30 FR             | 4480        |
| 40 FR             | 4000        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.