


# MULTIMAX MP 522

<b>TIRE SIZE</b>	<b>540/70 R 24</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	CARREGADORA COMPACTA / LEVANTADOR TELESCÓPICO / CARREGADORA COMPACTA / LEVANTADOR TELESCÓPICO
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	168 A8/B



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94052264	<b>RC (IN)</b>	162.7
<b>SW (IN)</b>	20.9	<b>RIM REC</b>	DW 16 L
<b>OD (IN)</b>	53.8	<b>RIM ALT</b>	DW 18 L
<b>SLR (IN)</b>	24.1	<b>ECE</b>	E11-106R-002967

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	23	29	35	41	46	51	58	61	64
30	5930	7040	8020	9140	10250	10990	12350	-	-
25	5930	7040	8020	9140	10250	10990	12350	-	-
20	6350	7540	8600	9790	10980	11770	13220	-	-
15	6590	7830	8920	10150	11390	12210	13710	-	-
5 CYC.	7230	8900	10470	12040	13710	14910	16850	17780	18520
STATIC	11080	13630	16050	18460	21020	22860	25850	27260	28390

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.