


# EARTHMAX SR 22



<b>TIRE SIZE</b>	<b>20.5 R 25</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MOTOLIVELLATRICE / PALA CARICATRICE / DOZER / PALA CARICATRICE / DOZER / MOTOLIVELLATRICE
<b>VERSIONE</b>	CUT RESISTANT COMPOUND
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	177 B ; 193 A2

## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94052431	<b>RIM REC</b>	17.00/2.0
<b>OD (IN)</b>	58.7	<b>RIM ALT</b>	17.00/1.7
<b>SLR (IN)</b>	25.2	<b>TRA CODE</b>	E2/L2
<b>RC (IN)</b>	169.9	<b>STAR RATING</b>	★★

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	58	62	65	69	73	76	80	83	87	91	94
30	12800	13600	14300	14800	15200	16100	-	-	-	-	-
5	-	-	-	-	-	21500	22000	22700	24000	24700	25400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.