


RIDEMAX FL 693 M



| | |
|---------------------|--|
| TIRE SIZE | 500/60 R 22.5 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | CAMIÓN CISTERNA / REMOLQUE / MAQUINARIA AGRÍCOLA |
| VERSIÓN | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 155 D ; 152 E |

DIMENSIONES IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 503 | RIM REC | AG 16.00 |
| OD (MM) | 1172 | RIM ALT | 15.00; 17.00 |
| SLR (MM) | 531 | ECE | E4-106R-001402 |
| RC (MM) | 3577 | SRI | 550 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.0 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 |
|------------|------|------|------|------|------|------|------|------|------|
| 70 | 1320 | 1495 | 1775 | 2095 | 2400 | 2665 | 2985 | 3270 | 3550 |
| 65 | 1435 | 1630 | 1940 | 2290 | 2620 | 2910 | 3255 | 3565 | 3875 |
| 50 | 1740 | 1970 | 2345 | 2770 | 3170 | 3520 | 3940 | 4315 | 4690 |
| 40 | 1955 | 2215 | 2635 | 3110 | 3560 | 3955 | 4430 | 4850 | 5270 |
| 25 | 2270 | 2575 | 3065 | 3615 | 4135 | 4595 | 5145 | 5635 | 6125 |
| 10 | 2585 | 2930 | 3490 | 4120 | 4710 | 5235 | 5860 | 6420 | 6975 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.