


AGRIMAX FORCE



TIRE SIZE	IF 650/60 R 34
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SKÖRDEMASKIN / MOTORSTARK TRAKTOR / TRAKTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	165 D

DIMENSIONER US STANDARD

USA CODE	94063628	RC (IN)	195.0
SW (IN)	25.6	RIM REC	DW 23 B
OD (IN)	64.7	RIM ALT	DW 21 B
SLR (IN)	29.4	ECE	E11-106R-006014

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	4740	5460	6290	7020	7840	8560	9590	10330
FROM 40 TO 25	5210	6010	6920	7720	8620	9410	10550	11355
20	5410	6240	7200	8020	8960	9790	10970	11810
12	5620	6480	7470	8330	9300	10160	11390	12260
5	6610	7630	8780	9800	10950	11950	13390	14420
*UPTO 5 CYC WITH FRONT LOADER	7300	8410	9690	10800	12060	13170	14760	15890
5 HT	5410	6240	7200	8020	8960	9790	10970	11810

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.