

XL GRIP (E3)



XL GRIP (E3)

XL GRIP (E-3) is a bias-ply tyre for rigid dump trucks designed to minimize cuts and punctures in severe conditions where exceptional traction is required. These features result in an extended tyre life.



	SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø25"	16.00 - 25	TL	E3/L3	32	-	11.25/2.0	13.00/2.0	0	465	1485	682	4395	29,5	STD
	18.00 - 25	TL	E3/L3	40		13.00/2.5	15.00/2.5	0	530	1615	739	4780	31.5	STD
	18.00 - 25	TT	E3/L3	32		13.00/2.5	15.00/2.5	0	530	1615	739	4780	31.5	STD
	18.00 - 25	TT	E3/L3	40		13.00/2.5	15.00/2.5	0	530	1615	739	4780	31.5	STD

STD: STANDARD

TECHNOLOGIES		PERFORMANCES	
			
			

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. BKT reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TKPH (TK/H)	OW (mm) 	OD (mm) 	SLR (mm) 	RC (mm) 	TREAD DEPTH (MM)	VERSION
					REC RIM	ALT RIM							
													
18.00 - 25	TT	E3/L3	24		13.00/2.5	15.00/2.5	0	530	1615	739	4780	31.5	STD
18.00 - 25	TL	E3/L3	16		13.00/2.5	15.00/2.5	0	530	1615	739	4780	31.5	STD
18.00 - 25	TL	E3/L3	32		13.00/2.5	15.00/2.5	0	530	1615	739	4780	31.5	STD
16.00 - 25	TL	E3/L3	28	-	11.25/2.0	13.00/2.0	0	465	1485	682	4395	29,5	STD
18.00 - 33	TL	E3	36	-	13.00/2.5	-	0	510	1820	840	5385	31,5	STD
18.00 - 33	TT	E3	32	-	13.00/2.5	-	0	510	1820	840	5385	31,5	STD
18.00 - 33	TL	E3	40		13.00/2.5	-	0	530	1820	840	5385	31.5	STD
18.00 - 33	TL	E3	32	-	13.00/2.5	-	0	510	1820	840	5385	31,5	STD

STD: STANDARD

TECHNOLOGIES	PERFORMANCES
  E3/L3	   

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026



TECHNOLOGIES		PERFORMANCES	
	 E3/L3		
			
-	-		

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026