

AS 504

| | |
|---------------------------|---|
| TIRE SIZE | 16.0/70 - 20 |
| UM | US STANDARD |
| CONSTRUCTION | |
| MACHINERY | TELEHANDLER / FIELD TRAILER / IMPLEMENTS / TELEHANDLER |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 142 A8 |
| LI/SS FREE ROLLING | 154 A8 |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|--------------------|
| USA CODE | 94019069 | RC (IN) | 126.5 |
| SW (IN) | 16.5 | RIM REC | 13 |
| OD (IN) | 43.2 | RIM ALT | 12 SDC; 14; 13 SDC |
| SLR (IN) | 19.2 | ECE | E4-106R-001876 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 51 |
|-----------|-------|
| 5 FR | 11570 |
| 15 FR | 9840 |
| 20 FR | 9260 |
| 25 FR | 8270 |
| 5 DW | 8180 |
| 15 DW | 6960 |
| 20 DW | 6550 |
| 25 DW | 5840 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.