

# SM 54 M IND-4S

|                     |                   |
|---------------------|-------------------|
| <b>TIRE SIZE</b>    | <b>18.00 - 25</b> |
| <b>UM</b>           | IS STANDARD       |
| <b>CONSTRUCTION</b> | ⊠ BIAS            |
| <b>MACHINERY</b>    | REACH STACKER     |
| <b>VERSÃO</b>       | PORT INDUSTRIAL   |
| <b>TIRE TYPE</b>    | TL                |



## DIMENSÕES IS STANDARD

|                 |           |                 |           |
|-----------------|-----------|-----------------|-----------|
| <b>OD (MM)</b>  | 1650      | <b>RIM ALT</b>  | 15.00/2.5 |
| <b>SLR (MM)</b> | 750       | <b>PR</b>       | 40        |
| <b>RC (MM)</b>  | 4880      | <b>TRA CODE</b> | IND-4S    |
| <b>RIM REC</b>  | 13.00/2.5 |                 |           |

## LOAD CAPACITY (KG/TIRE)

|                   |              |
|-------------------|--------------|
| <b>KM/H / BAR</b> | <b>10.00</b> |
| 10                | 22950        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.