


AW 711

TIRE SIZE	395/55 R 16.5
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HAY HARVESTER / IMPLEMENT MACHINERY / HARVESTER / IMPLEMENTS
VERSION	STUBBLE RESISTANT
TL/TT	TL
LI/SS	152 A8/B



DIMENSIONS US STANDARD

USA CODE	94053469	RC (IN)	99.1
SW (IN)	15.5	RIM REC	12
OD (IN)	33.0	ECE	E11-106R-002997
SLR (IN)	14.4		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52	58	73
30	2350	3050	3760	4310	5020	5720	6110	6730	7360	7830
25	2350	3050	3760	4310	5020	5720	6110	6730	7360	7830
20	2630	3430	4220	4830	5620	6420	6840	7550	8260	8770
15	2800	3640	4480	5130	5960	6800	7270	8010	8760	9310
10	2970	3860	4740	5430	6320	7210	7700	8490	9280	9870
5	3300	4280	5270	6030	7020	8000	8550	9420	10310	10960

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.