


# EARTHMAX SR 22

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>14.00 R 24</b>  |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | NIVELEUSE / CHARGEUR / BULLDOZER<br>/ CHARGEUR / BULLDOZER /<br>NIVELEUSE                |
| <b>VERSION</b>      | CUT RESISTANT COMPOUND   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 153 A8 ; 175 A2  |



## DIMENSIONS IS STANDARD

|                 |         |                    |                   |
|-----------------|---------|--------------------|-------------------|
| <b>OD (MM)</b>  | 1370    | <b>RIM ALT</b>     | 9.00 GR; 10.00 VA |
| <b>SLR (MM)</b> | 625     | <b>TRA CODE</b>    | G2/L2             |
| <b>RC (MM)</b>  | 4141    | <b>STAR RATING</b> | ★                 |
| <b>RIM REC</b>  | 8.00 TG |                    |                   |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 2.00 | 2.25 | 2.50 | 2.75 | 3.00 | 3.25 | 3.50 | 3.75 | 5.25 | 5.50 |
|------------|------|------|------|------|------|------|------|------|------|------|
| 40         | 2240 | 2430 | 2650 | 2800 | 3000 | 3250 | 3350 | 3650 | -    | -    |
| 10         | -    | -    | -    | -    | -    | -    | -    | -    | 6700 | 6900 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.