

# FLOTATION 648

<b>TIRE SIZE</b>	<b>385/65 - 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	PRESSE À PAILLE / MOISSONNEUSE / ÉPANDÉUR / MOISSONNEUSE / OUTILLAGE AGRICOLE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	155 A8/151 B
<b>LI/SS FREE ROLLING</b>	167 A8/163 B



## DIMENSIONS US STANDARD

<b>CODE USA</b>	94031443	<b>RC (IN)</b>	127.3
<b>SW (IN)</b>	15.7	<b>RIM REC</b>	AG 11.75
<b>OD (IN)</b>	42.1	<b>ECE</b>	E11-106R-004388
<b>SLR (IN)</b>	18.7	<b>PR</b>	22

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	77	81	86
<b>5 FR</b>	15810	16310	16820
<b>10 FR</b>	14220	14680	15130
<b>20 FR</b>	12640	13050	13460
<b>25 FR</b>	11290	11650	12010
<b>30 FR</b>	10160	10480	10750
<b>5 DW</b>	11230	11610	11960
<b>10 DW</b>	10110	10450	10770
<b>20 DW</b>	8980	9280	9570
<b>25 DW</b>	8020	8290	8540
<b>30 DW</b>	7220	7460	7610

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.