


# AGRIMAX RT 855

<b>TYRE SIZE</b>	<b>340/85 R 36</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SPRAYER / VINEYARD HARVESTER / TRACTOR / HARVESTER / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	132 A8/B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	353	<b>RIM REC</b>	W 12
<b>OD (MM)</b>	1492	<b>RIM ALT</b>	W 11
<b>SLR (MM)</b>	689	<b>ECE</b>	E4-106R-000763
<b>RC (MM)</b>	4507	<b>SRI</b>	725

## LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
50	1100	1280	1460	1640	1820	2000
40	1100	1280	1460	1640	1820	2000
30	1180	1370	1565	1755	1950	2140
10 LT	1475	1720	1960	2200	2440	2680
10 HT	1180	1370	1565	1755	1950	2140

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.