

# AT 621

**12.5/80 - 18****UM** IS STANDARD**CONSTRUCTION**  BIAS**MACHINERY** KÜÇÜK YÜKLEYİCİ / BEKOLODER /  
BEKOLODER / YÜKLEYİCİ**VERSION** STANDARD**TIRE TYPE** TL

129 A8

142 A8



## UNDEFINED IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 308  | <b>RIM REC</b> | W 9             |
| <b>OD (MM)</b>  | 987  | <b>RIM ALT</b> | 11.0            |
| <b>SLR (MM)</b> | 434  | <b>ECE</b>     | E11-106R-003388 |
| <b>RC (MM)</b>  | 2916 | <b>PR</b>      | 12              |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>3.70</b> |
|-------------------|-------------|
| 10 FR             | 3710        |
| 25 FR             | 3155        |
| 30 FR             | 2970        |
| 40 FR             | 2650        |
| 10 DW             | 2590        |
| 25 DW             | 2200        |
| 30 DW             | 2070        |
| 40 DW             | 1850        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.