

# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>280/85 R 24</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZADOR AGRÍCOLA / VINDIMADORA / TRATOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	115 A8/B



## DIMENSÕES IS STANDARD

<b>SW (MM)</b>	292	<b>RIM REC</b>	W 10
<b>OD (MM)</b>	1086	<b>RIM ALT</b>	W 9
<b>SLR (MM)</b>	492	<b>ECE</b>	E4-106R-000611
<b>RC (MM)</b>	3224	<b>SRI</b>	525

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
50	670	780	890	1000	1110	1215
40	670	780	890	1000	1110	1215
30	720	840	955	1075	1190	1305
10 LT	900	1045	1190	1340	1485	1630
10 HT	720	840	955	1075	1190	1305

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.