

# MP 600

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 400/70 - 24  |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> | ⊠ BIAS   |
| <b>MACHINERY</b>    | ARBETSFORDON / TELESKOPLASTARE<br>/ ARBETSFORDON /<br>TELESKOPLASTARE /<br>UNIVERSALFORDON |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |



## DIMENSIONER IS STANDARD

|                 |      |                |        |
|-----------------|------|----------------|--------|
| <b>SW (MM)</b>  | 405  | <b>RIM REC</b> | 13 SDC |
| <b>OD (MM)</b>  | 1185 | <b>RIM ALT</b> | 12     |
| <b>SLR (MM)</b> | 545  | <b>PR</b>      | 10     |
| <b>RC (MM)</b>  | 3530 |                |        |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>2.50</b> |
| 40 DW             | 2975        |
| 50 DW             | 2900        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.