


AGRIMAX RT 600

TIRE SIZE	650/75 R 32
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HARVESTER / SPREADER / TRACTOR / IMPLEMENTS
VERSION	STANDARD
TL/TT	TL
LI/SS	172 A8/B



DIMENSIONS IS STANDARD

SW (MM)	655	RIM REC	DW 21 B
OD (MM)	1789	RIM ALT	DW 20 B ; DW 23 B
SLR (MM)	807	ECE	E11-106R-004755
RC (MM)	5416	SRI	850

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.4	1.6	2.0	2.4	2.8	3.2	3.4	3.8
50	2900	3340	4095	4475	4915	5355	5800	6300	-	-
40	2900	3340	4095	4475	4915	5355	5800	6300	-	-
30	3105	3575	4385	4790	5265	5735	6210	6745	-	-
10 LT	3885	4480	5490	6000	6590	7180	7770	8445	-	-
10 HT	3105	3575	4385	4790	5265	5735	6210	6745	-	-
10 CYC.	-	4770	6105	6695	7765	8515	9320	10125	10285	10710

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.